



US006657427B2

(12) **United States Patent**
Åkerblom

(10) **Patent No.: US 6,657,427 B2**
(45) **Date of Patent: Dec. 2, 2003**

(54) **METHOD AND DEVICE FOR MEASURING A DISTANCE BETWEEN A STATOR AND A ROTOR**

(75) Inventor: **Bengt Åkerblom, Vårby (SE)**

(73) Assignee: **D/A Production AB, Skarholmen (SE)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/979,143**

(22) PCT Filed: **Mar. 20, 2001**

(86) PCT No.: **PCT/SE01/00572**

§ 371 (c)(1),
(2), (4) Date: **Nov. 20, 2001**

(87) PCT Pub. No.: **WO01/71276**

PCT Pub. Date: **Sep. 27, 2001**

(65) **Prior Publication Data**

US 2002/0158628 A1 Oct. 31, 2002

(30) **Foreign Application Priority Data**

Mar. 23, 2000 (SE) 0001031

(51) **Int. Cl.**⁷ **G01B 7/14**

(52) **U.S. Cl.** **324/207.26; 324/207.15**

(58) **Field of Search** 324/207.26, 207.11, 324/202, 207.13, 207.12, 229, 243, 242, 239, 227, 226, 207.15; 241/37, 30; 73/660, 661

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,434,670 A * 3/1969 May 241/37

3,848,814 A	*	11/1974	Syrjanen	241/37
3,898,562 A		8/1975	Mizikar et al.	324/758
4,454,991 A	*	6/1984	Brenholdt	241/30
4,627,578 A		12/1986	Whyte	241/30
4,727,322 A		2/1988	Lonchamp et al.	324/229
4,820,980 A	*	4/1989	Dodson-Edgars	324/207.24
4,878,020 A		10/1989	Kärnä et al.	324/207.17
5,691,636 A		11/1997	Allhouse et al.	324/207.15

FOREIGN PATENT DOCUMENTS

SE 401 896 6/1978

* cited by examiner

Primary Examiner—N. Le

Assistant Examiner—Reena Aurora

(74) *Attorney, Agent, or Firm*—Young & Thompson

(57) **ABSTRACT**

In a machine which is provided with a stator and an opposite rotor, a sensor of magnetic type, arranged in the stator, for determining the distance between the stator and the rotor can be calibrated by the sensor first being moved relative to the stator into contact with the rotor for zeroing. The sensor is then reversed a predetermined distance, after which the sensor signal can be used for determining the distance between the stator and the rotor. In an arrangement suitable for the purpose, the stator has at least one sensor of magnetic type, which is intended to interact with an opposite surface on the rotor. The sensor is mounted displaceably in the axial direction of the rotor and can be brought into contact with the rotor.

8 Claims, 1 Drawing Sheet

