



US007064536B2

(12) **United States Patent**
Akerblom et al.

(10) **Patent No.:** **US 7,064,536 B2**

(45) **Date of Patent:** **Jun. 20, 2006**

(54) **TRANSDUCER FOR DISTANCE MEASUREMENT**

(56) **References Cited**

(75) Inventors: **Bengt Akerblom**, Varby (SE); **Bengt Lofqvist**, Johanneshov (SE)

(73) Assignee: **Daprox AB**, Skarholmen (SE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 191 days.

(21) Appl. No.: **10/484,267**

(22) PCT Filed: **Sep. 24, 2002**

(86) PCT No.: **PCT/SE02/01734**

§ 371 (c)(1),
(2), (4) Date: **Jan. 20, 2004**

(87) PCT Pub. No.: **WO03/027607**

PCT Pub. Date: **Apr. 3, 2003**

(65) **Prior Publication Data**

US 2004/0169506 A1 Sep. 2, 2004

(30) **Foreign Application Priority Data**

Sep. 26, 2001 (SE) 0103199

(51) **Int. Cl.**
G01B 7/14 (2006.01)
G01B 7/30 (2006.01)
H01F 5/00 (2006.01)

(52) **U.S. Cl.** **324/207.15; 241/37**

(58) **Field of Classification Search** **324/207.11, 324/207.13, 207.22, 207.26, 207.15; 241/28, 241/30, 37, 259.1**

See application file for complete search history.

U.S. PATENT DOCUMENTS

2,548,599	A *	4/1951	Garr	241/37
2,978,599	A *	4/1961	Wilcox	310/168
3,848,814	A *	11/1974	Syrjanen	241/37
4,387,339	A *	6/1983	Akerblom	324/207.18
4,804,912	A	2/1989	Lysen	
4,820,980	A *	4/1989	Dodson-Edgars	324/207.24
5,544,819	A *	8/1996	Shepherd	241/37
5,691,636	A *	11/1997	Allshouse et al.	324/207.15
6,502,774	B1 *	1/2003	Johansson et al.	241/37
6,661,222	B1 *	12/2003	Twerdochlib	324/207.26
6,892,973	B1 *	5/2005	Johansson et al.	241/261.2
2002/0158628	A1 *	10/2002	Akerblom	324/207.26

FOREIGN PATENT DOCUMENTS

DE	100 00 272	7/2001
EP	0 640 395	3/1995
SE	401 896	9/1976

* cited by examiner

Primary Examiner—Bot Ledynh
Assistant Examiner—Kenneth J. Whittington
(74) *Attorney, Agent, or Firm*—Young & Thompson

(57) **ABSTRACT**

A transducer (10) for distance measurement, especially between a stator and a rotor in a refiner for paper pulp production, in which the transducer is of the magnetic type and has a tubular casing (17), the one end of which forms a measuring head (14), in which a measuring pole (15) is fitted in a holder (16) which is mounted in the end of the casing (17) and seals this. The holder (16), with a first portion (22) of its axial length, reaches beyond the end of the casing. This first portion (22) and the measuring pole (15) are intended to be able to be worn away to a smaller axial length during use of the transducer, whilst the length of the casing is maintained.

11 Claims, 2 Drawing Sheets

