



US007830136B2

(12) **United States Patent**
Åkerblom et al.

(10) **Patent No.:** **US 7,830,136 B2**
(45) **Date of Patent:** **Nov. 9, 2010**

(54) **METHOD AND ARRANGEMENT FOR MOUNTING A SENSOR DESIGNED FOR MEASURING THE DISTANCE BETWEEN STATOR AND ROTOR**

(75) Inventors: **Bengt Åkerblom**, Vårby (SE); **Jonas Ollmar**, Bandhagen (SE)

(73) Assignee: **Daprox AB** (SE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 230 days.

(21) Appl. No.: **11/921,630**

(22) PCT Filed: **May 22, 2006**

(86) PCT No.: **PCT/SE2006/050145**

§ 371 (c)(1),
(2), (4) Date: **Dec. 5, 2007**

(87) PCT Pub. No.: **WO2006/135331**

PCT Pub. Date: **Dec. 21, 2006**

(65) **Prior Publication Data**

US 2009/0128137 A1 May 21, 2009

(30) **Foreign Application Priority Data**

Jun. 14, 2005 (SE) 0501346

(51) **Int. Cl.**
G01R 33/02 (2006.01)

(52) **U.S. Cl.** **324/207.13; 73/660**

(58) **Field of Classification Search** **324/207.13; 73/660**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,293,695 A 3/1994 Olshefsky

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0640395 A1 3/1995

(Continued)

OTHER PUBLICATIONS

"PCT Application No. PCT/SE2006/050145, International Search Report mailed Oct. 2, 2006", 3 pgs.

(Continued)


Primary Examiner—Reena Aurora

(74) *Attorney, Agent, or Firm*—Schwegman, Lundberg & Woessner, P.A.

(57) **ABSTRACT**

The invention relates to a sensor (6) for measuring the distance between a stator and a rotor, which sensor is of the magnetic type and has a sensor body (8) to which is attached a sensor tip (10). The tip of the sensor (10) is connected to the sensor body (8) by a fixing arrangement (14) that has a locking device (16) that interacts with engaging devices (24) and a spring arrangement (34). The locking device (16) is pressed towards an attaching position (A) by the action of a spring force F1 exerted by means of the spring arrangement (34) against the engaging device (24), fixing the sensor body (8) and the tip of the sensor (10) in relation to each other. By the application of a force F2 on the sensor body (8) that is greater than the spring force F1, it is possible to move the sensor body and the tip of the sensor to a releasing position (D), releasing them in relation to each other.

14 Claims, 3 Drawing Sheets



US 7,830,136 B2

Page 2

U.S. PATENT DOCUMENTS

6,657,427 B2 12/2003 Aakerblom
2004/0169506 A1 9/2004 Akerblom et al.

FOREIGN PATENT DOCUMENTS

GB 2335748 A 9/1999
SE 520322 C2 6/2003

WO WO-2004/085070 A1 10/2004
WO WO-2006/135331 A1 12/2006

OTHER PUBLICATIONS

"PCT Application No. PCT/SE2006/050145, Written Opinion mailed Oct. 2, 2006", 4 pgs.
"European Application Serial No. 06733514.1, Communication dated Dec. 30, 2009", 3 pgs.