




- (51) International Patent Classification:  
*D21D 1/30* (2006.01)      *D21B 1/14* (2006.01)  
*B02C 7/12* (2006.01)      *D21B 1/36* (2006.01)
- (21) International Application Number:  
PCT/SE2015/050134
- (22) International Filing Date:  
6 February 2015 (06.02.2015)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
1450143-1      11 February 2014 (11.02.2014)      SE
- (71) Applicant: DAPROX AB [SE/SE]; Jägerhorns väg 19, S-141 75 Kungens Kurva (SE).
- (72) Inventor: ÅKERBLOM, Bengt; Vårby Allé 23, S-143 40 Vårby (SE).
- (74) Agents: ZACCO SWEDEN AB et al.; Box 5581, S-114 85 Stockholm (SE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:  
— with international search report (Art. 21(3))

(54) Title: A REFINER APPARATUS AND A METHOD FOR REFINING CELLULOSIC MATERIAL



(57) Abstract: The present invention regards a refiner plate segment (1) for a disc-type refiner apparatus (30), adapted to grind a saturated cellulosic material (M) in a refining gap (17) defined by opposed discs (20) during use of the apparatus (30), the material being moved from a refiner inlet opening (21) towards an outer edge (7) of the segment (1). The outer edge (7) of the segment (1) comprises a barrier arrangement (15) to increase the pressure in the refining gap (17) for retaining the liquid phase out to said outer edge (7). The present invention also regards a method of refining a saturated cellulosic material (M) in a refining gap (17) defined by two opposed discs (20) of a disc arrangement.

